

# 16K ADJUSTABLE HD CL16

This 16,000 lbs. 2-Post Lift boasts optimum flexibility and meets ALI®/ANSI® safety standards. It features **adjustable column extensions to accommodate three settings for height** from either 13' 6" to 14' 6" or add 2' column extensions to go from 15' 6" to 16' 6". **Standard features include 3-stage front and rear arms and low-profile arm supports for a full swing.**

12' 10<sup>3</sup>/<sub>4</sub>"



13' 4<sup>3</sup>/<sub>4</sub>"



13' 10<sup>3</sup>/<sub>4</sub>"



**13' 6" MINIMUM**



**16' RECOMMENDED**



**28' RECOMMENDED**



**208-230V, 1PH, 30A**



**90-120 PSI**



MODEL NUMBER	CL16-3S				CL16-2-3S		
Description	16K Standard			16K Extended Height			
Lifting Capacity	16,000 lbs.						
Lift Configuration	Symmetric						
Arm Configuration	3-Stage Front & Rear						
Max. Load Per Arm	4,000 lbs.						
Rise Height Max. with Stack Adapters	Min. 75½" Max. 81½"						
Overall Height Options	13' 6"	14'	14' 6"	15' 6"	16'	16' 6"	
Drive-Thru Clearance	9' 8¼"	9' 2¼"	8' 8¼"	9' 8¼"	9' 2¼"	8' 8¼"	
Floor to Overhead Switch	12' 11"	13' 5"	13' 11"	14' 11"	15' 5"	15' 11"	
Arm Reach	Min. 36⅝" Max. 75"						
Screw Pad Height	Min. 4¾" Max. 6½"						
Between Columns	Standard - 10'   +6" - 10' 6"   +12" - 11'						
Rise Time	62s						
Min. Ceiling Height Required	13' 8"	14' 2"	14' 8"	15' 8"	16' 2"	16' 8"	
ALI® Certified	☑						

