

20K HD ADJUSTABLE CL20-0 / CL20-2

Engineered to be wider, taller, and more robust, the CL20 is here to tackle the heaviest vehicles in your fleet.

SERVICE BAY SPECIFICATIONS

- HEIGHT:** 13' 6" minimum
- WIDTH:** 16' recommended
- DEPTH:** 28' recommended
- POWER:** 208-230v, 1pH, 30a
- AIR:** 90-120 psi

CONCRETE
4" thick, reinforced, free from cracks/seams,
3500+ psi & cured 28+ days



PRODUCT SPECIFICATIONS

MODEL NUMBER	CL20-0			CL20-2		
Description	20K Standard			20K Extended Height		
Lifting Capacity	20,000 lbs.					
Lift Configuration						
Arm Configuration	2-Stage Front & Rear					
Max. Load Per Arm	5,000 lbs.					
Rise Height	Min. 76 $\frac{1}{16}$ " Max. 84 $\frac{1}{16}$ " (with stack adapters)					
Overall Height Options	13' 6"	14'	14' 6"	15' 6"	16'	16' 6"
Floor to Overhead Switch	12' 11"	13' 5"	13' 11"	14' 11"	15' 5"	15' 11"
Arm Reach	Min. 38½" Max. 62"					
Screw Pad Height	Min. 6¾" Max. 7⅞"					
Between Columns	Standard - 10' +6" - 10' 6" +12" - 11'					
Rise Time	62s					
ALI® Certified	☒					

SERVICE BAY LAYOUT

