

10K 2-POST SA10

Challenger Lifts 10,000 lb. 2-Post lift, the SA10, features the ability to be installed in either a symmetric or an asymmetric (turn column) configuration to suit the service requirements of your particular shop.

SERVICE BAY SPECIFICATIONS

-  **HEIGHT:** 12' minimum
-  **WIDTH:** 14' recommended
-  **DEPTH:** 24' recommended
-  **POWER:** 208-230v, 1pH, 20a

CONCRETE
4" thick, reinforced, free from cracks/seams,
3500+ psi & cured 28+ days



SPECIFICATIONS

MODEL NUMBER	SA10			
Lift Configuration	Symmetric	Symmetric w/ 2' ext SA10EH2	Asymmetric	Asymmetric w/ 2' ext SA10EH2
Rise Height	74 $\frac{7}{8}$ "			
Overall Height	11' 10 $\frac{1}{2}$ "	13' 10 $\frac{1}{2}$ "	11' 10 $\frac{1}{2}$ "	13' 10 $\frac{1}{2}$ "
Overall Width	10' 9" or 11' 3"		10' 11 $\frac{1}{2}$ " or 11' 5 $\frac{1}{2}$ "	
Drive Thru Clearance	7' 8 $\frac{3}{4}$ " or 8' 2 $\frac{3}{4}$ "		7' 4 $\frac{1}{2}$ " or 7' 10 $\frac{1}{2}$ "	
Floor to Overhead Switch	10' 11 $\frac{1}{8}$ " / 11' 5 $\frac{1}{8}$ "	12' 11 $\frac{1}{8}$ " / 13' 5 $\frac{1}{8}$ "	10' 11 $\frac{1}{8}$ " / 11' 5 $\frac{1}{8}$ "	12' 11 $\frac{1}{8}$ " / 13' 5 $\frac{1}{8}$ "
Front Arm Reach	Min 22 $\frac{3}{8}$ " Max 41 $\frac{1}{2}$ "			
Rear Arm Reach	Min 38 $\frac{1}{4}$ " Max 59"			
Screw Pad Height	Min 4 $\frac{3}{4}$ " Max 6 $\frac{7}{8}$ "			
Rise Time	44s			
Required Ceiling Height	12'	14'	12'	14'
ALI® Certified	☒			

SERVICE BAY LAYOUT

