





7.7K SCISSOR LIFT

DX77


The DX77 offers free access all around the vehicle, and between platforms, with a cross-member-free design providing an uncluttered and hazardous-free work area.

REQUIREMENTS

-  **12' MINIMUM**
-  **12' RECOMMENDED**
-  **28' RECOMMENDED**
-  **208-230V, 1PH, 30A**

CONCRETE
4" thick, reinforced, free from cracks/seams,
3500+ psi & cured 28+ days



 MODEL # DX77

SPECIFICATIONS

MODEL NUMBER	DX77	DX77-R
Description	Standard	Flush Mount
Lifting Capacity	7,700 lbs.	
Overall Width (A)	82"	69½"
Width Between Platforms (B)	21" - 27"	
Platform Width (C)	24½"	
Platform Length (D)	59"	
Ramp Length (E)	11¾"	
Rise Height (F)	74½"	70"
Overall Length (G)	83¼"	
Lowered Height (H)	4½"	NA
Max. Wheelbase	NA	
Wheel Alignment	NA	
Standard Motor/Voltage	2HP, 208-220v, 60Hz, 1Ph	
Rise Time	43s	
Max. Load per Platform	3,850 lbs.	
ALI® Certified	<input checked="" type="checkbox"/>	

SERVICE BAY LAYOUT

