

10K INGROUND EV1020

With its small footprint and substantial capabilities, this 10,000 lbs., 3-Stage inground lift is ready for any professional service facility.

REQUIREMENTS



12' MINIMUM



12' RECOMMENDED



24' RECOMMENDED



208-230V, 1PH, 30A



90-120 PSI



MODEL # EV1020



All Ingrounds are fully contained to eliminate any risk of environmental impact.

MODEL NUMBER	EV1020 / EV1020-QC	EV1020XP9 / EV1020XP9-QC
Description	Standard / QuickCycle™	XP9 / XP9 & QuickCycle™
Lifting Capacity	10,000 lbs.	9,000 lbs.
Arm Configuration	3-Stage Front & Rear	Drive-on Express Pad
Stroke	68"	
Rise Height	74"	70"
Overall Width (A)	97"	79½"
Drive Thru Clearance (B)	7' 3"	NA
Arm Reach (C)	Min. 19⅝" Max. 42⅞"	NA
Platform Length x Width	NA	58"/66½"/75" x 24"
Distance Between Platforms	NA	31½"
Screw Pad Height	3⅞" - 6⅞"	NA
Plunger Diameter	8½"	
Standard Motor/Voltage*	2HP, 208v-230v, 60Hz, 1Ph / 3HP, 208v-230v, 60Hz, 1Ph	
Rise Time	38s / 24s	38s / 24s
Max. Load per Arm	2,500 lbs.	4,500 lbs.
ALI® Certified	☒	

