

10K & 12K WIDE INGROUND

EW1020 & EW1220

Our new wide inground lifts provide the necessary drive-through clearance for servicing wide-bodied, exotic, and electric vehicles.

REQUIREMENTS

- 12' MINIMUM**
- 12' RECOMMENDED**
- 24' RECOMMENDED**
- 208-230V, 1PH, 30A**

CONCRETE
4" thick, reinforced, free from cracks/seams,
3500+ psi & cured 28+ days



SPECIFICATIONS

MODEL NUMBER	EW1020 / EW1020-QC	EW1220 / EW1220-QC
Description	Standard / QuickCycle™	Standard / QuickCycle™
Lifting Capacity	10,000 lbs.	12,000 lbs.
Arm Configuration	3-Stage Front & Rear	
Stroke	72"	
Rise Height (A)	78"	
Overall Width (B)	117½"	121½"
Drive Thru Clearance (C)	88"	
Arm Reach (D)	Min. 20" Max. 42"	Min. 20⅞" Max. 48½"
Screw Pad Height	4" - 6⅞"	
Plunger Diameter	8½"	
Standard Motor/Voltage*	2HP, 208v-230v / 3HP, 208v-230v	
Rise Time	41s / 24s	63s / 38s
Max. Load per Arm	2,500 lbs.	3,000 lbs.
Required Ceiling Height	12'	
ALI® Certified	☒	

